

# Schedule 4: Motor Coach (30 days or 12 000 km) Inspections

(Items to be inspected are numbered below, with the major defects identified.)

#	Item to be inspected	Major Defects
1	Air brake system	<ul style="list-style-type: none"> <li>•audible air leak</li> <li>•brake pushrod stroke at or beyond adjustment limit</li> <li>•clearance between disc brake pads and rotor exceeds manufacturer's specified limit</li> <li>•wedge brake shoe movement exceeds manufacturer's specified limit</li> <li>•excessive discharge of fluids from air reservoir</li> <li>•air compressor, mounts or attachments damaged or defective</li> <li>•compressor drive-belt loose or damaged</li> <li>•air line or fitting damaged or insecure</li> <li>•air tank defective, damaged or insecure</li> <li>•air tank drain or moisture ejector device inoperable</li> <li>•brake chamber, brake linkage or other brake component defective, damaged or insecure</li> <li>•spring brake broken or malfunctions</li> <li>•inoperative service, parking or emergency brake</li> </ul>
2	Exhaust system	<ul style="list-style-type: none"> <li>•exhaust leak</li> <li>•exhaust system component insecure, damaged or perforated</li> </ul>
3	Frame and/or underbody	<ul style="list-style-type: none"> <li>•any frame member or fastener damaged, cracked or insecure</li> <li>•any component mount damaged or insecure</li> </ul>
4	Fuel system	<ul style="list-style-type: none"> <li>•fuel leak</li> <li>•insecure fuel tanks, fuel tank mounts or guards</li> <li>•fuel line or fitting damaged or insecure</li> </ul>
5	Steering	<ul style="list-style-type: none"> <li>•steering linkage damaged or insecure</li> <li>•power steering fluid leaking, contaminated or low</li> <li>•power steering component damaged or insecure</li> </ul>
6	Suspension system	<ul style="list-style-type: none"> <li>•air leak or malfunction of air suspension system or component</li> <li>•damage or deterioration of any suspension component, including               <ul style="list-style-type: none"> <li>- spring and air bag</li> <li>- axle- or frame-attaching component</li> <li>- axle supporting or aligning component</li> <li>- suspension or component fastener</li> <li>- shock absorber or attachments</li> </ul> </li> </ul>
7	Tires	<ul style="list-style-type: none"> <li>•tire inflation less than required</li> <li>•tire treads worn to wear limits</li> <li>•damage to tread or sidewall of tire</li> <li>•retread or rebuilt tire used on front axle</li> </ul>
8	Wheels and fasteners	<ul style="list-style-type: none"> <li>•loose, missing, damaged or ineffective wheel fastener</li> <li>•damaged wheel or wheel component</li> </ul>